

SINGLE COURT LAYOUT

DOUBLE COURT LAYOUT

GENERAL NOTES

- DESIGN IS BASED UPON A MINIMUM FLOW OF 48 GPM AND A MINIMUM PRESSURE OF 75 PSI DOWNSTREAM OF BACKFLOW PREVENTION DEVICE.
- 2. ADDITIONAL LATERALS OUTSIDE PLAY FIELD AREA MAY BE INSTALLED PROVIDED HYDRAULIC CAPABILITY OF SUPPLY IS NOT EXCEEDED.
- 3. SPRINKLER LOCATIONS ARE TO SCALE. PIPE LOCATIONS ARE DIAGRAMMATIC.
- 4. PROVIDE #55K-1 KEY (1" MALE OUTLET) AND SH-2 SWIVEL HOSE ELL FOR EACH QUICK COUPLING VALVE.

LEGEND

		QUANTITY
H	BACKFLOW PREVENTION DEVICE	1
\otimes	MAIN SHUT-OFF VALVE	1
•	RAIN BIRD ELECTRIC REMOTE CONTROL VALVE (SIZED AS SHOWN) SINGLE COURT LAYOUT DOUBLE COURT LAYOUT	2 3
•	RAIN BIRD 5LRC QUICK COUPLING VALVE SINGLE COURT LAYOUT DOUBLE COURT LAYOUT	1 2
Ø	RAIN BIRD 7005 W/12 NOZZLE PRESSURE = 60 PSI RADIUS = 59 FEET FLOW = 12 GPM SINGLE COURT LAYOUT DOBLE COURT LAYOUT	6 9
$\langle \mathbf{A} \rangle$	RAIN BIRD IRRIGATION CONTROLLER W/12 STATION	S 1


MAINLINE PIPE: CLASS 200 PVC (2-INCH SIZE)

— LATERAL PIPE: CLASS 200 PVC (SIZED AS SHOWN)

A1 INDICATES CONTROLLER AND CONTROLLER STATION NUMBER

24 INDICATES LATERAL DISCHARGE IN GPM

1" INDICATES REMOTE CONTROL VALVE SIZE



TENNIS

GRASS OR CLAY

7005

SPRINKLERS

Date:		

Drawing Number:

TC-C



Rain Bird presents this plan as a typical sports field layout. Rain Bird offers no indemnity, expressed or implied, for projects installed from this plan. Since each site and system contains many variables, Rain Bird expressely recommends the use of a qualified irrigation designer.