

## Pig Tail

NEW

### PIGTAIL

#### Primary Application

Use with outdoor controllers, this UL approved pig tail meets most local codes.

#### Features

- 6-feet (1,8 m) long
- Three 16 gauge stranded conductor wires
- 90 degree molded plug type Nema 5-15P
- Gray color

#### Model

- PIGTAIL

## Pump Start Relay

### RELAY-100, R-200

#### Primary Application

Activates pump motors using irrigation controllers. Use the RELAY-100 for activating pump motors up to 1-1/2 HP and the R-200 for motors up to 5 HP. Both relays are UL approved!

#### Features

- NEMA type 3R rainproof (outdoor or indoor mount)
- Pre-installed 2 low voltage and 4 high voltage lead wires
- 6 wire nuts included
- R-200 uses reliable Square D technology

#### Specifications

##### Relay-100

- UL approved
- Coil Operating Voltage: 24 VAC
- Contact Rating:
  - 1½ HP at 240 VAC
  - 1 HP at 120 VAC
  - 20 amps at 240 VAC
- Coil Input Rating: 26.5 VAC maximum @ 0.175 amps

##### R-200

- UL approved
- Coil Operating Voltage: 24 VAC
- Contact Rating:
  - 5 HP at 230 VAC
  - 2 HP at 115 VAC
  - 30 amps at 230 VAC
- Coil Input Rating: 26.7 VAC maximum @ 0.256 amps

#### Model

- RELAY-100: Pump start relay for up to 1½ HP motors
- R-200: Pump start relay for up to 5 HP motors

## Pump Thermal Shut-Off

NEW

### PTS

#### Primary Application

Use to automatically shut-off pumps before overheat damage occurs. Protects against lost prime, pressure switch failure, closed valves, stuck relays, low water tables and loose fittings.

#### Features

- Mounts in any position
- Heavy duty UL approved thermostat
- Automatic shutoff and reset
- Use with pump motors up to 2 HP

#### Specifications

- Automatic 120°F (49°C) shut-off
- Automatic 110°F (43°C) reset
- Wire inline 24/110/220 VAC
- 30 amps max.

#### Model

- PTS



PIGTAIL



R-200



PTS